

ILS or LOC RWY 29
ST LOUIS RGNL (ALN)

MISSED APPROACH: Climb to 1000 then climbing right turn to 2200 on heading 310° and on TOY VORTAC R-322 to TOPAZ INT/TOY 16 DME and hold.

ALTERNATE MISSED APCH FIX


SQUAR INT I-ALN 12.1

114°

294°

117.4 STL R-051 Chan 121

108.5 I-ALN R-294 Chan 22



	TOY R-322	TOPAZ INT	*LOC only.	
			OSERE INT I-ALN [6.2]	QUNIE INT I-ALN [13]
				JACOB I-ALN [19]
			2100	2100
			*980	2100
				← 294° → 2100
				GS 3.00° TCH 55
CATEGORY	A	B	C	D
S-ILS 29	731-½ 200 (200-½)			
S-LOC 29	980-½	449 (500-½)	980-⅞	449 (500-⅞)
CIRCLING	1000-1	456 (500-1)	1160-1¾ 616 (700-1¾)	1200-2 656 (700-2)
WULIB FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 29	880-½	349 (400-½)	880-5⁄8	349 (400-5⁄8)
CIRCLING	1000-1	456 (500-1)	1160-1¾ 616 (700-1¾)	1200-2 656 (700-2)

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

ST LOUIS RGNL (ALN)
ILS or LOC RWY 29