

RNAV (GPS) RWY 22
ARTESIA MUNI (ATS)

T For uncompensated Baro-VNAV systems, procedure NA below -22°C
A or above 54°C.

Climb to 4600 then climbing left turn to 6000 direct WUNTO and hold.

UNICOM
123.075 (CTAF) **L**

CHISUM CME

6500
128°
(21.7)

(IAF) SIPDE

5 NM

036°

216°

HOLD

12000
6000

6000 NoPT
156° (5)

5200
216°
(6.1)

(IF/IAF) WUNTO

276°
(5)

6000 NoPT

(IAF) FIXAV

7000
284°
(51.4)

HOBBS HOB

605' A

RW22

(FAF) GUCCY

7000
352°
(30.3)

ROHYO

Procedure NA for arrival on HOB VORTAC
airway radials 234 CW 276.

4767

Procedure NA for arrival
on HOB VORTAC
airway radials 234 CW 276.

4600
↑

6000
↖

WUNTO
✦

* LNAV only.

* 1.1 NM to RW22

RW22

GUCCY 5200

WUNTO

5 NM Holding Pattern

036° → 12000
← 216° 6000

216°

5200

GP 3.00°
TCH 40

		1.1 NM	4.1 NM	6.1 NM	
CATEGORY		A	B	C	D
LPV	DA	3772-1			250 (300-1)
LNAV/ VNAV	DA	3772-1			250 (300-1)
LNAV	MDA	3880-1			358 (400-1)
 CIRCLING		3960-1 415 (500-1)	4000-1 455 (500-1)	4040-1½ 495 (500-1½)	4240-2¼ 695 (700-2¼)

MIRL Rwy 4-22 and 13-31 L

ARTESIA MUNI (ATS)
RNAV (GPS) RWY 22