

LOC I-BRD
109.9

APP CRS
231°

Rwy Idg
TDZE **1224**
Apt Elev **1232**

ILS or LOC RWY 23
BRainerd Lakes RGNL (BRD)

ADF required. When local altimeter setting not received, use Aitkin altimeter setting and increase all DAs 52 feet and all MDAs 60 feet. Increase S-LOC Cat C visibility to 1 SM and Circling Cat D visibility to 2¼ SM.

MALSRR

AS

MISSED APPROACH: Climb to 2100 then climbing right turn to 3000 direct LAREW LOM and hold.

ASOS
126.775

MINNEAPOLIS CENTER
118.05 239.0

UNICOM
122.7 (CTAF) 1

1892

3000 (19.6)

HUUTA
(RNAV 1-GPS REQD)

MSA BR 25 NM
3100

ADF REQUIRED

18°

298°

BRNRD

LOCALIZER
I-BRD
109.9

051°
1 min
231°
1429
3000 358° (6.6)
BRNRD
(RNAV 1-GPS REQD)

LOM/IAF
LAREW
251 BR

1696 A

1771

1281

1384

1771

BRNRD
(RNAV 1-GPS REQD)

2100
3000
BR

BR LOM
2976
051°
231°
3000
GS 3.00°
TCH 50
5.3 NM

One Minute Holding Pattern

CATEGORY	A	B	C	D
S-ILS 23	1424-½ 200 (200-½)			
S-LOC 23	1680-½ 456 (500-½)	1680-¾ 456 (500-¾)	1680-1 456 (500-1)	
CIRCLING	1760-1 528 (600-1)	1760-1½ 528 (600-1½)	1860-2 628 (700-2)	

ELEV 1232
TDZE 1224

91
7100 X 150
231°
1267 A
1300
34
5

1267 A
1300
34
5

HIRL Rws 5-23 and 16-34
REIL Rws 5 and 16

FAF to MAP 5.3 NM

Knots

60 90 120 150 180

Min:Sec

5:18 3:32 2:39 2:07 1:46

BRainerd, Minnesota

Amdt 7A 29MAR18

46°24'N-94°08'W

BRainerd Lakes RGNL (BRD)
ILS or LOC RWY 23

NC-1, 22 FEB 2024 to 21 MAR 2024

NC-1, 22 FEB 2024 to 21 MAR 2024