

LOC I-JOU 111.1	APP CRS 210°	Rwy Idg 8999 TDZE 1430 Apt Elev 1430
---------------------------	------------------------	---

ILS or LOC RWY 21

JOE FOSS FLD (FSD)

For inoperative MALSR increase S-ILS all Cats visibility to ¾ mile,
increase S-LOC 21 Cat C/D visibility to 1⅞ mile. When using
WADRI FIX minimums, increase S-LOC 21 Cat C/D visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 3400
then right turn direct FSD VORTAC
and hold.

ATIS 126.6	SIoux FALLS APP CON * 125.8 306.2	SIoux FALLS TOWER * 118.3 (CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95
----------------------	---	--	-------------------------------	-------------------------

ELEV 1430

TDZE 1430

3400

FSD

JOESY OM/INT

One Minute Holding Pattern

*LOC only.

WADRI INT FSD 3.6

3047

030°

210°

3100

3100

GS 3.00°

TCH 49

2 NM

2.9 NM

CATEGORY	A	B	C	D
S-ILS 21	1630/18 200 (200-½)			
S-LOC 21	2100/24	670 (700-½)	2100-1½	670 (700-1½)
CIRCLING	2100-1	670 (700-1)	2100-1¾ 670 (700-1¾)	2200-2½ 770 (800-2½)
WADRI FIX MINIMUMS				
S-LOC 21	1800/24	370 (400-½)	1800/35	370 (400-¾)
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)

SIoux FALLS

TDZ/CL Rwy 21

REIL Rwys 15 and 33

MIRL Rwy 9-27

HIRL Rwys 3-21 and 15-33

FAF to MAP 4.9 NM

Knots

60

90

120

150

180

Min:Sec

4:54

3:16

2:27

1:58

1:38

SIoux FALLS, SOUTH DAKOTA

Amdt 10C 18JUN20

43°35'N-96°45'W

JOE FOSS FLD (FSD)

ILS or LOC RWY 21