


APP CRS 212°	Rwy Idg TDZE Apt Elev	11002 2346 2385
------------------------	-----------------------------	--


RNAV (RNP) Z RWY 21
SPOKANE INTL (GEG)

RNP AR APCH.  For uncompensated Baro-VNAV systems, procedure NA below -19°C or above 43°C. For inop ALS increase RNP 0.11 visibility all Cats to ¾, RNP 0.15 visibility all Cats to 1% and RNP 0.30 visibility all Cats to 1% .		ALS-F-2 	MISSED APPROACH: Climb to 5000 on track 212° to IRUHO and on track 252° to GANGS and hold. *Missed approach requires minimum climb of 310 feet per NM to 3000.	
ATIS 124.325 254.375	SPOKANE APP CON 123.75 282.25 (205°-025°) 133.35 263.0 (026°-204°)	SPOKANE TOWER 118.3 278.3	GND CON 121.9 348.6	CLNC DEL 127.55



CATEGORY	A	B	C	D
RNP 0.11 DA*		2596/24	250 (300-½)	
RNP 0.15 DA		2699/30	353 (400-⅝)	
RNP 0.30 DA		2752/45	406 (400-⅞)	

AUTHORIZATION REQUIRED



TDZ/CL Rwy 3 and 21
REIL Rwy 8 and 26
HIRL Rwy 3-21
MIRL Rwy 8-26

AUTHORIZATION REQUIRED