

|                                        |                        |                                                                 |
|----------------------------------------|------------------------|-----------------------------------------------------------------|
| WAAS<br>CH <b>61216</b><br><b>W20A</b> | APP CRS<br><b>200°</b> | Rwy Idg <b>6100</b><br>TDZE <b>3786</b><br>Apt Elev <b>3788</b> |
|----------------------------------------|------------------------|-----------------------------------------------------------------|

RNAV (GPS) RWY 20  
HEREFORD MUNI (H.R.X)




RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 41°C (105°F).

▲ When local altimeter setting not received, use Rick Husband Amarillo Intl altimeter setting: Increase LPV DA to 4098 feet and all Cats visibility ¼ SM, increase LNAV/VNAV DA to 4232 feet and all Cats visibility ¼ SM, increase all MDA 120 feet; increase LNAV Cats C/D visibility ½ SM, increase Circling Cat C visibility ½ SM and Cat D visibility ¼ SM. Baro-VNAV NA when using Rick Husband Amarillo Intl altimeter setting. VDP NA with Rick Husband Amarillo Intl altimeter setting.

MISSED APPROACH:  
Climb to 6000 direct  
LEMG and hold.

|                         |                                          |                                 |
|-------------------------|------------------------------------------|---------------------------------|
| AWOS-3<br><b>118.05</b> | AMARILLO APP CON ★<br><b>119.5 307.0</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|-------------------------|------------------------------------------|---------------------------------|



| CATEGORY   | A                          | B           | C                             | D                             |
|------------|----------------------------|-------------|-------------------------------|-------------------------------|
| LPV DA     | 3986-3/4 200 (200-3/4)     |             |                               |                               |
| LNAV/ VNAV | 4120-1 1/4 334 (400-1 1/4) |             |                               |                               |
| LNAV MDA   | 4220-1                     | 434 (500-1) | 4220-1 1/4                    | 434 (500-1 1/4)               |
| CIRCLING   | 4280-1                     | 492 (500-1) | 4440-1 3/4<br>652 (700-1 3/4) | 4620-2 3/4<br>832 (900-2 3/4) |

