

WAAS CH 53623 W18A	APP CRS 179°	Rwy Idg TDZE 1115 Apt Elev 1115
--	------------------------	---

RNAV (GPS) RWY 18


OSCEOLA MUNI (I75)

⚠

Baro-VNAV NA when using Chariton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When VGSI inop, Straight-In/Circling Rwy 18 procedure NA at night. DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Chariton altimeter setting and increase all DA 44 feet and all MDA 60 feet.

MISSED APPROACH:
Climb to 3000 direct FEBKY and hold.

AWOS-3 120.975	DES MOINES APP CON 123.9 360.7	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 1115		TDZE 1115	
179°		81	
4001 X 75		36	
MIRL Rwy 18-36		REIL Rwy 18 and 36	
3000		FEBKY	
*LNAV only.		WUMIP 2 NM to RW18	
RW18		RAXFE	
2 NM		2.9 NM	
1780*		2700	
2 NM		5.1 NM	
CATEGORY		A	
LPV DA		1365-1 250 (300-1)	
LNAV/VNAV DA		1365-1 250 (300-1)	
LNAV MDA		1460-1 345 (400-1)	
CIRCLING		1580-1 465 (500-1)	