

WAAS
CH **56206**
W17A

APP CRS
175°

Rwy Idg **8006**
TDZE **213**
Apt Elev **214**

RNAV (GPS) RWY 17

BOB SIKES (CEW)

RNP APCH.


▼

▲

Circling NA for Cat D west of Rwy 17-35. Baro-VNAV and VDP NA when using EGLIN AFB altimeter setting. When local altimeter setting not received, use Eglin AFB altimeter setting and increase LPV DA to 529, LNAV/VNAV DA to 699 and all MDA 60 feet. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C.

MISSED APPROACH: Climb to 2000 direct HEKLU and hold.

ASOS 119.275	EGLIN APP CON 124.05 284.65	UNICOM 122.95 (CTAF) 0
------------------------	---------------------------------------	----------------------------------



4 NM Holding Pattern

WEDOM

GIYAT

HEKLU

6000

2000

GP 3.00°

TCH 51

355°

175°

175°

1500

1500

1500

1.2 NM to RW17

RW17

6 NM

2.6 NM

1.2 NM

*1.2 NM to RW17

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	470-1 257 (300-1)			
LNAV/VNAV DA	640-1½ 427 (500-1½)			
LNAV MDA	660-1 447 (500-1)	660-1¼ 447 (500-1¼)	660-1½ 447 (500-1½)	
CIRCLING	700-1 486 (500-1)	820-1¾ 606 (700-1¾)	840-2 626 (700-2)	

ELEV 214

TDZE 213

175°

1.2% DOWN

8006 X 150

0.3% UP

35

HIRL Rwy 17-35 0

WAAS CH 40208 W35A	APP CRS 355°	Rwy Idg 8006 TDZE 163 Apt Elev 214
--	------------------------	---

RNAV (GPS) RWY 35

BOB SIKES (CEW)

RNP APCH.


▼

⚠

Baro-VNAV and VDP NA when using Eglin AFB altimeter setting. Rwy 35 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. When local altimeter setting not received, use Eglin AFB altimeter setting and increase LPV DA to 509, LNAV/VNAV DA to 550, and all MDA 60 feet, increase LNAV Cat C/D visibility ½ SM.

MISSED APPROACH: Climb to 2000 direct WEDOM and hold.

ASOS 119.275	EGLIN APP CON 124.05 284.65	UNICOM 122.95 (CTAF) 0
------------------------	---------------------------------------	----------------------------------



ELEV 214

TDZE 163

2000

WEDOM

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 61).

4 NM Holding Pattern

HEKLU

175° → 6000
← 355° 2000

GP 3.00°
TCH 52

*LNAV only.

*1.3 NM to RW35

1600

355°

1600

1.3 NM

3 NM



6 NM

CATEGORY	A	B	C	D
LPV DA	450-1 287 (300-1)			
LNAV/VNAV DA	491-1¼ 328 (300-1¼)			
LNAV MDA	640-1 477 (500-1)		640-1⅜ 477 (500-1⅜)	

VOR-A
BOB SIKES(CEW)



MISSED APPROACH: Climb to 1200 then climbing left turn to 2200 direct CEW VORTAC and hold.

UNICOM
122.95 (CTAF) **L**

One Minute Holding Pattern

CEW VORTAC

1200

2200

CEW

6000 ← 286°

2200 106° →

NOTME CEW 7.3

MADEW CEW 8.3

* 960 when using Eglin AFB altimeter setting.

106°

* 900

7.3 NM

1 NM

CATEGORY	A	B	C	D
C CIRCLING	900-1	686 (700-1)	900-2 686 (700-2)	900-2¼ 686 (700-2¼)

NOTME FIX MINIMUMS (ADF OR DME REQUIRED)

C CIRCLING	700-1	486 (500-1)	820-1¼ 606 (700-1¼)	840-2 626 (700-2)
-------------------	-------	-------------	------------------------	----------------------