



ILS or LOC RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

T Autopilot coupled approach NA below 1700. Rwy 23 helicopter visibility reduction below RVR 4000 NA. Inop table does not apply to S-ILS 23. For inop ALS, increase S-LOC 23 Cat A/B visibility to RVR 5500, and Cat C/D to 2 SM.

MISSED APPROACH:
Climb to 1800 then climbing
right turn to 3000 direct
HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
---------------	-------------------------------------	---------------------------------	------------------------	--------------------



Autopilot coupled approach NA below 1300.

MISSED APPROACH: Climb to 1800 then climbing left turn to 3500 direct HVQ VOR/DME and hold.

ATIS

127.6

CHARLESTON APP CON

124.1 269.125

CHARLESTON TOWER

125.7 257.8

GND CON

121.8 348.6

CLNC DEL

118.55

One Minute Holding Pattern		SHOAL INT I-HCV 11.9 RADAR		KANCO INT I-HCV 6 RADAR		ZVRU INT I-HCV 2.1		I-HCV DME ANTENNA		UCYUZ I-HCV 0.1							
5400 ← 232°		3500 → 052°		2900		1640		1800		3500							
GS 3.00° TCH 56		2900		1640		1800		3500		HVQ							
5.9 NM		3.9 NM		1 NM		1 NM		0.1									
CATEGORY	A	B	C	D													
S-ILS 5	1197/40		250 (300-¾)														
S-LOC 5	1640/55	693 (700-1)		1640-2	693 (700-2)												
CIRCLING	1640-1	693 (700-1)		1760-2½	813 (900-2½)		1880-3	933 (1000-3)									
ZVRU FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)																	
S-LOC 5	1320/55		373 (400-1)														
CIRCLING	1600-1	653 (700-1)		1760-2½	813 (900-2½)		1880-3	933 (1000-3)									

ELEV 947

TDZE 947

6715 X 150

0-18% UP

TWR 1037

052°

HIRL Rwy 5-23

REIL Rwys 5

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58

CHARLESTON, WEST VIRGINIA

Orig-B 05OCT23


WEST VIRGINIA INTL YEAGER (CRW)

ILS or LOC RWY 5


38°23'N-81°36'W

RNAV (RNP) Z RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

MISSED APPROACH:
Climb to 4000 on track
233° to CITMA and hold.

CLNC DEL
118.55

See planview for multiple IF locations.




CATEGORY	A	B	C	D
RNP 0.30 DA	1419/60 488 (500-1¼)			

AUTHORIZATION REQUIRED

ELEV 947	D	TDZE 931
----------	----------	----------

D

 TDZE | 931 |

HIRL Rwy 5-23
REIL Rwy 5

APP CRS
053°

Rwy Idg
6215

TDZE
947

Apt Elev
947

RNAV (RNP) Z RWY 5


WEST VIRGINIA INTL YEAGER (CRW)

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems,
procedure NA below -17°C or above 54°C.

MISSED APPROACH: Climb to 3000
on track 053° to ENVY and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
----------------------	--	--	-------------------------------	---------------------------



JETVO
3000

See planview for multiple IF locations.

3000
↑
tr 053°

ENVY

3000
↘
053°

RW05

GP 3.00°
TCH 56

6.3 NM

ELEV 947

D

TDZE 947

6715 X 150

0.8% UP

TWR 1037

053°

CATEGORY	A	B	C	D
RNP 0.10 DA		1197/40	250 (300-¾)	
RNP 0.30 DA		1607-178	660 (700-178)	

AUTHORIZATION REQUIRED

HIRL Rwy 5-23
REIL Rwy 5

WAAS
CH **45616**
W23A

APP CRS
233°

Rwy Idg
TDZE
Apt Elev
6215
931
947

RNAV (GPS) Y RWY 23
WEST VIRGINIA INTL YEAGER (CRW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inoperative ALSF, increase LNAV/VNAV all Cats visibility to 2¼. **RVR 1800 authorized with use of FD or AP or HUD to DA.

ALSF-1

(A1)

MISSED APPROACH: Climb to 1400 then dimbing right turn to 3000 direct HVQ VOR/DME and hold.

ATIS 127.6	CHARLESTON APP CON 124.1 269.125	CHARLESTON TOWER 125.7 257.8	GND CON 121.8 348.6	CLNC DEL 118.55
----------------------	--	--	-------------------------------	---------------------------

Procedure NA for arrivals at Wardo on V59 northbound.

Procedure NA for arrival on HVQ VOR/DME airway radials 360 CW 141.

Procedure NA for arrivals at ITALY on V59 northbound.

MSA RW23 25 NM

4400

ELEV 947

D

TDZE 931

233°

6715 x 150

0.8% UP

(A1)

TWR 1037

1400

3000

HVQ

*LNAV only.

ZUPUT 2.3 NM to RW23

COSIK 2400

ENIVY 6 NM Holding Pattern

1.7 NM to RW23

*1680

2400

GP 3.00° TCH 56

CATEGORY

A

B

C

D

LPV

DA**

1131/24

200 (200-½)

LNAV/VNAV

DA

1601-1⅞

670 (700-1⅞)

LNAV

MDA

1500/24

569 (600-½)

1500-1⅓

569 (600-1⅓)

C CIRCLING

1600-1

653 (700-1)

1760-2½

813 (900-2½)

1760-2¾

813 (900-2¾)

CHARLESTON, WEST VIRGINIA
Amdt 1B 07DEC17

38°23'N-81°36'W


WEST VIRGINIA INTL YEAGER (CRW)
RNAV (GPS) Y RWY 23

VOR/DME HVQ	APP CRS	Rwy Idg TDZE	N/A
117.4	084°		N/A
Chan 121		Apt Elev	947

VOR-A

WEST VIRGINIA INTL YEAGER (CRW)

⚠ ⚠		MISSED APPROACH: Climb to 1800 then climbing left turn to 3500 direct HVQ VOR/DME and hold.		
ATIS	CHARLESTON APP CON	CHARLESTON TOWER	GND CON	CLNC DEL
127.6	124.1 269.125	125.7 257.8	121.8 348.6	118.55



One Minute Holding Pattern		HVQ VOR/DME		1800 	3500 	HVQ 
10000 3000		← 264° 084° →		FOGAG HVQ 6		
		084°		MACSA HVQ 8		
		1720				
		6 NM		2 NM		
CATEGORY	A	B	C	D		
 CIRCLING	1720-1	773 (800-1)	1760-2½ 813 (900-2½)	1880-3 933 (1000-3)		
FOGAG FIX MINIMUMS (DME REQUIRED)						
 CIRCLING	1600-1	653 (700-1)	1760-2½ 813 (900-2½)	1880-3 933 (1000-3)		

