

RNP APCH.

▼

Rwy 36 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

▲


Circling NA for Cats C and D West of Rwy 18-36.

MISSED APPROACH: Climb to 4100 direct HANUK and hold, continue to climb-in-hold to 4100.

AWOS-3
120.625

RAZORBACK APP CON *
120.9 343.75

UNICOM
122.8 (CTAF) 0



5 NM Holding Pattern		JOBOK		HAPIK		CLOMP 3.1 NM to RW36		4100 HANUK	
6000 ← 187° 4100 → 007°		007°		2400		*1.1 NM *LNAV only. to RW36		RW36	
GP 3.05° TCH 40				2400		*1500			
		5.6 NM		2.8 NM		2 NM		1.1	
CATEGORY	A	B	C	D					
LPV DA	701-1		250 (300-1)						
LNAV/VNAV DA	786-1		335 (400-1)						
LNAV MDA	840-1 389 (400-1)		840-1½ 389 (400-1½)						
CIRCLING	1000-1 549 (600-1)		1100-1 649 (700-1)		1100-1¾ 649 (700-1¾)		1160-2¼ 709 (800-1¼)		

ELEV 451 TDZE 451

REIL Rwy 36
MIRL Rwy 18-36

81

4007 X 75

36

007° to RW36