

APP CRS
180°

Rwy Idg
TDZE
Apt Elev

9320
295
341

RNAV (RNP) X RWY 18R

MEMPHIS INTL (MEM)

▼

For uncompensated Baro-VNAV systems, procedure NA below -9°C (16°F) or above 48°C (118°F). Simultaneous approach authorized. GPS required. Missed approach requires RNP less than 1.0. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 180° to ZUPIN and on track 180° to HARUB and on track 180° to JAGUR and on track 223° to JEPOB and hold.

MEMPHIS APP CON			MEMPHIS TOWER			GND CON		
119.1	291.6	(176°-355°)	(Rwy 9-27)	118.3	257.8	(Rwy 9-27)	121.0	379.2
125.8	338.3	(356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7	257.8	(Rwys 18C-36C, 18L-36R)	121.9	379.2
			(Rwy 18R-36L)	128.425	257.8	(Rwy 18R-36L)	121.65	379.2

D-ATIS	CLNC DEL	CPDLC
127.75	125.2	

RADAR REQUIRED

ELEV 341	TDZE 295
----------	----------

5000	ZUPIN	HARUB	JAGUR	JEPOB
↑	tr 180°	tr 180°	tr 180°	tr 223°

MCVEY

ELVIS

RW18R

2000

180°

4400

GP 3.00°

TCH 52

CATEGORY	A	B	C	D
RNP 0.14 DA	737/45 442 (400-7%)			

AUTHORIZATION REQUIRED

MEMPHIS, TENNESSEE

MEMPHIS INTL (MEM)

Orig-E 29MAR18

35°03'N-89°59'W

RNAV (RNP) X RWY 18R