

LOC I-JNK

109.1

APP CRS

319°

Rwy Idg

6500

TDZE

937

Apt Elev

937

ILS or LOC RWY 32

DELAWARE COUNTY RGNL (MIE)

When control tower closed, except for operations with approved weather reporting use Fort Wayne altimeter setting. For inop MALSR when using Fort Wayne altimeter setting minimums, increase S-ILS 32 visibility to 1 SM. When local altimeter setting not received, use Fort Wayne altimeter setting: increase DA to 1257 feet and visibility all Cats ¼ SM; increase all MDAs 120 feet and visibility Cat C ½ SM, Cat D 1 ½ SM. VDP NA when using Fort Wayne altimeter setting.

MALSR

MISSED APPROACH: Climb to 1460 then climbing right turn to 2900 direct BALL LOM and hold.

ATIS 133.25	INDIANAPOLIS APP CON 120.65 317.8	MUNCIE TOWER ★ 120.1 (CTAF) 0	GND CON 121.9	UNICOM 122.95
----------------	--------------------------------------	----------------------------------	------------------	------------------

ADF or DME REQUIRED

ELEV 937

D

TDZE 937

1460

2900

JN

*LOC only.

*MIE 1.4

2462

2900

2500

139°

319°

GS 3.00°

TCH 52

1

2

3

5198 X 100

6500 X 150

TWR 1018

319°

HIRL Rwy 14-32

MIRL Rwy 3-21

REIL Rws 3, 14 and 21

FAF to MAP 4.6 NM

Knots

60

90

120

150

180

Min:Sec

4:36

3:04

2:18

1:50

1:32

CATEGORY	A	B	C	D
S-ILS 32	1137-½ 200 (200-½)			
S-LOC 32	1380-½	443 (500-½)	1380-¾	443 (500-¾)
CIRCLING	1460-1	523 (600-1)	1500-1½	1600-2
			563 (600-1½)	663 (700-2)
FORT WAYNE ALTIMETER SETTING MINIMUMS				
S-ILS 32	1257-⅝ 320 (400-⅝)			
S-LOC 32	1520-½	583 (600-½)	1520-1½	1520-2½
			583 (600-1½)	583 (600-2½)
CIRCLING	1580-1	643 (700-1)	1600-1¾	1720-2½
			663 (700-1¾)	783 (800-2½)

MUNCIE, INDIANA

Amdt 9E 31DEC20

40°15'N-85°24'W

DELAWARE COUNTY RGNL (MIE)

ILS or LOC RWY 32