

WAAS CH 69227 W32A	APP CRS 321°	Rwy Idg TDZE Apt Elev	3511 10 10
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 32

MICHAEL J SMITH FLD (MRH)


⚠

⚠


DME/DME RNP-0.3 NA. ATC clearance required to penetrate R-5306A and R-5306C. When local altimeter setting not received, use Cherry Point MCAS (Cunningham Fld) altimeter setting and increase all MDA 40 feet; increase LP Cats C and D visibility ½ mile. Straight-in Rwy 32 NA at night, Circling Rwy 8, 14, 32 NA at night. Rwy 8, 14, 32 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 direct ISUJU and on track 326° to EWN VOR/DME and hold.

ASOS 135.375	CHERRY POINT APP CON 132.575 268.7	CLNC DEL 125.65	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------	---------------------------------



ELEV 10	TDZE 10
---------	---------



3000	ISUJU	tr 326°	EWN	
RW32 EXAVE LAVTE 6 NM Holding Pattern				
3.00° TCH 40 1000 3 NM 6 NM				
CATEGORY	A	B	C	D
LP MDA	380-1 370 (400-1)			
LNAV MDA	460-1 450 (500-1)		460-1 3/8 450 (500-1 3/8)	
CIRCLING	540-1 530 (600-1)		580-1 1/2 570 (600-1 1/2) 580-2 570 (600-2)	

SE-2, 22 FEB 2024 to 21 MAR 2024

SE-2, 22 FEB 2024 to 21 MAR 2024