

APP CRS	Rwy Idg	8700
227°	TDZE	50
	Apt Elev	55

RNAV (RNP) Z RWY 23

RHODE ISLAND TF GREEN INTL (PVD)

▼

For uncompensated Baro-VNAV systems, procedure NA below -15°C (5°F) or above 48°C (118°F). RF required. For inop MALSR, increase RNP 0.30 all Cats visibility to 1¼. GPS Required.

MALSR

Climb to 2500 on track 227° to WIKIT and right turn to STUFY and on track 013° to FOSTY and hold.

D-ATIS 124.2	PROVIDENCE APP CON ★ 123.675 244.875	PROVIDENCE TOWER ★ 120.7 (CTAF) 257.8	GND CON 121.9 348.6	CLNC DEL 126.65 348.6
-----------------	---	--	------------------------	--------------------------

RADAR REQUIRED

ELEV 55 TDZE 50

TDZ/CL Rwy 5
REIL Rwy 16
HIRL Rws 5-23 and 16-34

2500 WIKIT

tr 227°

STUFY

tr 013°

FOSTY

HSBRO

1400

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 41).

See planview for multiple IF locations.

GP 3.00° TCH 51

CATEGORY	A	B	C	D
RNP 0.30 DA	434/40 384 (400-¾)			

AUTHORIZATION REQUIRED

PROVIDENCE, RHODE ISLAND

Orig-A 26JUN14

41°43'N-71°26'W

RHODE ISLAND TF GREEN INTL (PVD)

RNAV (RNP) Z RWY 23