

APP CRS
274°

Rwy Idg
TDZE
Apt Elev

7604
1068
1099

RNAV (RNP) Z RWY 27

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

For uncompensated Baro-VNAV systems, procedure NA below -17°C (2°F) or above 54°C (130°F). RF required. GPS required. Missed approach requires RNP less than 1.0. For inop ALS increase *RNP 0.10 DA visibility all Cats to RVR 4500 and RNP 0.30 DA visibility all Cats to 1 1/2 SM. DATVE transition NA when R-6714 A, C, D active.

MALSRR

MISSED APPROACH: Climb to 5100 on track 274° to YEPCU left turn to JOPDI left turn to ZEMUN left turn to MUDLE and hold.
* Missed approach requires a minimum climb of 215 feet per NM to 4300.

ATIS 125.25	SPOKANE APP CON* 123.8 263.15	YAKIMA TOWER* 133.25 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95
----------------	----------------------------------	--	------------------	-------------------	------------------

ELEV 1099 TDZE 1068

TWR 1159

7604 X 130

3835 X 150

274°

5100 YEPCU

JOPDI

ZEMUN

MUDLE

OAKSS 2900

See planview for multiple IF locations.

RW27

274°

5.6 NM

2900

GP 3.00°

TCH 57

CATEGORY	A	B	C	D
RNP 0.10 DA*	1348/24 280 (300-1/2)			
RNP 0.30 DA	1468/45 400 (400-7/8)			

AUTHORIZATION REQUIRED

YAKIMA, WASHINGTON

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

Orig-C 01MAR18

46°34'N-120°33'W

RNAV (RNP) Z RWY 27